

## CC HEAVY DUTY P-CLIPS POLYOLEFIN (PVC)

The Global Clamps CC Heavy Duty P-Clip range is proudly made in Australia and ideally suited for fastening cables and hoses in the toughest conditions. Applications and markets include Electrical, Hydraulic, Mining, Fire, Industrial, Marine and OEM's.

With unique features the Global Clamps CC Heavy Duty P-Clip range defines a new standard for traditional PVC P-Clips in the market today.

### Features & technical details:

- Galvabond band material in accordance with AS1397 / G2 Z275 Standards
- Band thicknesses 0.8mm / 1.2mm
- Band widths 19mm / 25mm
- Bolt hole sizes 10mm / 13mm
- Size stamped with both metric and imperial sizes for easy identification
- Size ranges from 6.0mm (0.25") to 90.0mm (3.56")
- Heavy duty dual wall polyolefin insulator sleeve with inner adhesive
- Chemical bond between insulator sleeve and band
- Insulator sleeve wall thickness 0.85mm / 1.0mm (tolerance of 0mm / +0.15mm)
- Available in black or red
- Rated for cables max 600V
- Working temperature -55°C to +125°C
- Tested in accordance with VW-1 flammability requirements. Recognized by both UL and CSA standards
- Available in multiple packaging options
- Assortment Kits complete with popular sizes are also available.

**For more information call us today.**




**CC W1 PO / PVC 19mm Band Width**

Product Description	Band Width / Bolt Hole mm	Diameter Range mm	Imperial Size In	Imperial Size In
CC 06x19-W1 PO	19/10	6	1/4	0.25
CC 10x19-W1 PO	19/10	10	3/8	0.38
CC 11x19-W1 PO	19/10	11	7/16	0.44
CC 12x19-W1 PO	19/10	12	15/32	0.47
CC 13x19-W1 PO	19/10	13	1/2	0.50
CC 14x19-W1 PO	19/10	14	9/16	0.57
CC 16x19-W1 PO	19/10	16	5/8	0.63
CC 18x19-W1 PO	19/10	18	11/16	0.69
CC 19x19-W1 PO	19/10	19	3/4	0.75
CC 21x19-W1 PO	19/10	21	13/16	0.81
CC 22x19-W1 PO	19/10	22	7/8	0.87
CC 24x19-W1 PO	19/10	24	15/16	0.94
CC 25x19-W1 PO	19/10	25	1	1.00
CC 27x19-W1 PO	19/10	27	11/16	1.06
CC 29x19-W1 PO	19/10	29	1 1/8	1.13
CC 32x19-W1 PO	19/10	32	1 1/4	1.25

**CC W1 PO / PVC 25mm Band Width**

Product Description	Band Width / Bolt Hole mm	Diameter Range mm	Imperial Size In	Imperial Size In
CC 29x25-W1 PO	25/13	29	1 1/8	1.13
CC 30x25-W1 PO	25/13	30	1 3/16	1.19
CC 32x25-W1 PO	25/13	32	1 1/4	1.25
CC 33x25-W1 PO	25/13	33	1 5/16	1.31
CC 36x25-W1 PO	25/13	36	7/16	1.44
CC 38x25-W1 PO	25/13	38	1 1/2	1.5
CC 40x25-W1 PO	25/13	40	1 9/16	1.56
CC 45x25-W1 PO	25/13	45	1 3/4	1.75
CC 46x25-W1 PO	25/13	46	1 13/16	1.81
CC 51x25-W1 PO	25/13	51	2	2.00
CC 52x25-W1 PO	25/13	52	2 1/16	2.06
CC 57x25-W1 PO	25/13	57	2 1/4	2.25
CC 64x25-W1 PO	25/13	64	2 1/2	2.50
CC 67x25-W1 PO	25/13	67	2 5/8	2.63
CC 70x25-W1 PO	25/13	70	2 3/4	2.75
CC 73x25-W1 PO	25/13	73	2 7/8	2.88
CC 90x25-W1 PO	25/13	90	3 9/16	3.56



[WWW.GLOBALCLAMPS.COM.AU](http://WWW.GLOBALCLAMPS.COM.AU)

**Disclaimer:** The information contained in this brochure is for general information purposes only, and is provided by Global Clamps Pty Ltd. Whilst we try at all times to keep the information up to date and correct, we cannot and do not in any way guarantee or give any assurances as to the completeness or accuracy of the information provided.